


钟振DIP08-500.000KHZ

Features


- voltage(1.8V~5.0V)
- Output Waveform(TTL)
- Supports a WIDE FREQUENCY RANGE(20K to 800MHZ)
- Output Voltage:0.4~2.4VDC
- Compact with dimensions of 12.8×12.8×5.0mm




Specifications

项目Item	技术Specifications	
输出波形 Output Waveform	方波 (TTL)	
频率范围Freq. Range	500.000KHZ	
频率稳定性Frequency Stability	$\pm 10\text{PPm}$, $\pm 20\text{PPm}$, $\pm 30\text{PPm}$, $\pm 50\text{PPm}$	
工作温度Operaing Temp	-20°C to 70°C (-40°C to 85°C available)	
储存温度Storage Temp	-55°C to 125°C	
输出波形对称性 Output Symmetry	40-60%@1.4VDC (45-55% available)	
电压Input Voltage:VDD	$+5.0\text{Vdc} \pm 5\%$ or $+3.3\text{Vdc} \pm 5\%$ available	
电流Input Current:IDD	100KHz to 70MHz, $\leq 20\text{mA}$	
	70MHz to 200MHz, $\leq 40\text{mA}$	
	$\geq 200.00\text{MHz}$, $\leq 60\text{mA}$	
上升时间Rise Time	TR	$\leq 6\text{ns}$
上降时间Fall Time	TF	$\leq 6\text{ns}$
输出电压Output Voltage	VOL	0.4Vdc Max.
	VOH	2.4Vdc Min.
输出负载Output Load	10LSTTL	
启动时间Start up Time	$< 10\text{ms}$	
老化能力 Agek Resistance	$\pm 3\text{PPm Max}$	


Ordering Information




输出波形图




■Dimensions



■测试电路图



■使用电路图和引出端功能说明



引脚	1	2
功能	输出状态控制/NC	地VSS
引脚	3	4
功能	输出QOUT	电源VDD
输出控制端 INHB	“H”高电平或 开路OPEN	
输出Qout	振荡器正常 输出	“L” 低电平 (三态) 高阻抗
注意：输出状态控制端INHB（三态端）不能接地，否则振荡器呈高阻抗		